

06-29-00

A

JCS30 U.S. PTO
06/28/00

PTO
09/05/99
06/28/00

LIMBACH & LIMBACH L.L.P.
2001 Ferry Building, San Francisco, CA 94111
415/433-4150

Address to:

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

Attorney's Docket No. SUGI-T0731

First Named Inventor YASUAKI YAMAGISHI

UTILITY PATENT APPLICATION TRANSMITTAL
(under 37 CFR 1.53(b))

SIR:

Transmitted herewith for filing is the patent application entitled:
TRANSMITTING APPARATUS, TRANSMITTING METHOD, RECEIVING APPARATUS, RECEIVING
METHOD, TRANSMITTING AND RECEIVING SYSTEM, AND TRANSMITTING AND RECEIVING
METHOD

CERTIFICATION UNDER 37 CFR § 1.10

I hereby certify that this New Application and the documents referred to as enclosed herein are being
deposited with the United States Postal Service on this date June 28, 2000, in an envelope bearing
"Express Mail Post Office To Addressee" Mailing Label Number EL254155479US addressed to: Box
Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Elizabeth Reicker

Elizabeth Reicker

(Name of person mailing paper)

(Signature)

Enclosed are:

1. X Transmittal Form (two copies required)
2. The papers required for filing date under CFR § 1.53(b):
 - i. 92 Pages of specification (including claims and abstract);
 - ii. 29 Sheets of drawings.

X formal informal
3. Declaration or oath
 - a. X Unsigned

ACCOMPANYING APPLICATION PARTS

4. An assignment of the invention to Sony Corporation is attached (including Form PTO-1595).
 - i. 37 CFR 3.73(b) Statement (when there is an assignee)
5. X Power of Attorney (unsigned)
6. An Information Disclosure Statement (IDS) is enclosed, including a PTO-1449 and copies of references.
7. Preliminary Amendment.
8. X Return Receipt Postcard (MPEP 503 -- should be specifically itemized)
9. FOREIGN PRIORITY
 - [x] Priority of application no. P11-186785 filed on June 30, 1999 in Japan is claimed under 35 USC 119.

The certified copy of the priority application:

- X is filed herewith; or
 - has been filed in prior application no. filed on , or
 - will be provided.
- English Translation Document (if applicable)

10. FEE CALCULATION

- a. ☐ Amendment changing number of claims or deleting multiple dependencies is enclosed.

CLAIMS AS FILED

	Number Filed	Number Extra	Rate	Basic Fee (\$690)
Total Claims	32 - 20	* 12	x \$18.00	216.00
Independent Claims	6 - 3	* 3	x \$78.00	234.00
Multiple dependent claim(s), if any			\$260.00	0

*If less than zero, enter "0".

Filing Fee Calculation \$1,140.00

50% Filing Fee Reduction (if applicable) \$

11. Small Entity Status

- a. ☐ A small entity statement is enclosed.
b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
c. ☐ is no longer claimed.

12. Other Fees

- ☐ Recording Assignment [\$40.00] \$0
☐ Other fees \$0
Specify _____ \$0

Total Fees Enclosed \$1,140.00

13. Payment of Fees

- ☒ Check(s) in the amount of \$ 1,140.00 enclosed.
☐ Charge Account No. 12-1420 in the amount of \$ ____.
A duplicate of this transmittal is attached.

14. All correspondence regarding this application should be forwarded to the following attorney:

Charles P. Sammut
Limbach & Limbach L.L.P.
2001 Ferry Building
San Francisco, CA 94111
Telephone: 415/433-4150
Facsimile: 415/433-8716


15. Authorization to Charge Additional Fees

- ☒ The Commissioner is hereby authorized to charge any additional fees (or credit any overpayment) associated with this communication and which may be required under 37 CFR § 1.16 or § 1.17 to Account No. 12-1420. A duplicate of this transmittal is attached.

LIMBACH & LIMBACH L.L.P.

June 28, 2000
(Date)

Attorney Docket No. SUGI-T0731
(SOOP0731US00)

By: 
Mayumi Maeda
Registration No. 40,075
Attorney(s) or Agent(s) for Applicant(s)

[illegible]

Inventor(s): Yasuaki YAMAGISHI
Kazuhiko TAKABAYASHI
Kazuo HARAOKA
Yoshihisa GONNO
Fumihiko NISHIO

TRANSMITTING APPARATUS, TRANSMITTING METHOD, RECEIVING APPARATUS, RECEIVING METHOD, TRANSMITTING AND RECEIVING SYSTEM, AND TRANSMITTING AND RECEIVING METHOD

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a transmitting apparatus, a transmitting method, a receiving apparatus, a receiving method, a transmitting and receiving apparatus, and a transmitting and receiving method suitable for broadcasting hierarchical data that is distributed on a network.

Description of the Related Art

Many data delivering methods have been proposed. For example, http (Hyper Text Transfer Protocol) is used to publish pages on the Internet. TCP/IP (Transmission Control Protocol/Internet Protocol) enables computers connected to the Internet to exchange data. In the TCP/IP, a receiving side that receives data calls a transmitting side. Whenever data is transmitted or received corresponding to the TCP/IP, a connection is established between the receiving side and the transmitting side. Thus, with such protocols, data can be delivered with high reliability. On the other hand, the transmitting side and the network are adversely loaded and thereby data cannot be effectively delivered.

In other words, when the number of terminal

units that receive data is becoming large and they access a server that delivers data thereto at a time, the server and the network are adversely loaded. Thus, even if a terminal unit requests the server for data, the terminal unit cannot receive the requested data from the server in a short time.

To solve such a problem, a method using a satellite line, a CATV (Cable Television) line, a ground wave digital broadcast, and so forth that allows data to be broadcast has been proposed. With this method, even if the number of terminal units increases, the server and the network are prevented from being adversely overloaded.

In recent years, as digital communication networks such as the Internet have become common, a huge amount of data has been stored on the networks. Thus, it is desired to effectively use such data. To do that, a directory service for hierarchically managing data distributed on a network and providing the data to the user is becoming popular. Using the directory service, the user can quickly find desired information from data distributed on the network and access the desired information.

The directory service has been set forth as X.500 series in OSI (Open System Interconnection) that is an international standard. In the X.500, the directory is defined as a set of open systems.

Individual open systems cooperatively have logical databases of information with respect to a set of objects of the real world.

5 With major directory services defined in the X.500, the user can search and browse information stored in the directory. The directory services also provide the user with a list service (such as a telephone directory) and a user authenticating service. In the directory service, each object is assigned a
10 unique name so that the user can easily memorize, infer, and recognize each object.

The directory services defined in the X.500 are very comprehensive. The program size of each directory service is very large. Thus, it is very
15 difficult to accomplish a directory service on the Internet that uses the TCP/IP as a protocol. To solve such a problem, LDAP (Lightweight Directory Access Protocol) has been proposed as a compact type directory service for the TCP/IP.

20 In recent years, a directory service using a broadcast data transmitting means such as a satellite line, a CATV line, a ground digital broadcast, or the like has been proposed. In this case, information is uni-directionally delivered with the directory service.
25 Thus, the user cannot request the directory service for desired data. Consequently, in such a directory service, the same information is repeatedly

transmitted. The user side stores received information to an IRD (Integrated Receiver Decoder) or an STB (Set Top Box) that is a digital broadcast receiver connected to a television receiver.

5 Next, information synchronization between the directory server side and the user side (namely, synchronization management) will be considered. The directory server side detects a substantial update of the directory corresponding to a dynamic change of the hierarchical structure of the directory. The directory server side transmits directory information corresponding to the change of the hierarchical structure of the directory to the user. At this point, only the difference of the changed data rather than all
10 directory information is extracted and transmitted.
15

 The directory server side transmits difference update data to the user whenever the directory server side detects an update of the directory information or at intervals of a
20 predetermined time period. When the user side always receives the difference update data corresponding to an update of the directory and updates the stored directory information with the received difference update data, the directory information is synchronized
25 between the directory server and the user.

 Now, it is assumed that the user side is in a pause state (for example, the power of the receiver is

turned off) and cannot receive difference update data from the directory server for a predetermined time period. For example, as shown in Fig. 1, the directory server successively transmits difference update data Msg1, Msg2, and Msg3 to the user. The difference update data Msg2 is the difference of the directory information updated by the difference update data Msg1. The difference update data Msg3 is the difference of the directory information updated by the difference update data Msg2.

To solve such a problem, for example, an overall structure of a directory is transmitted from the directory server to the user side at intervals of a predetermined time period. Difference update data against the received overall structure is transmitted in the above described manner. However, when the overall directory structure is frequently transmitted, the transmitting resources are wastefully used. Thus, in the conventional method, the advantageous feature of which difference update data is transmitted becomes meaningless.

OBJECTS AND SUMMARY OF THE INVENTION

Therefore, an object of the present invention is to provide a transmitting apparatus, a transmitting method, a receiving apparatus, a receiving method, a transmitting and receiving apparatus, and a transmitting and receiving method that allow an overall

directory structure to be broadcast without a loss of transmitting resources so as to update directory information without a mismatch between the transmitting side and the receiving side even if the receiving side cannot temporarily receive difference update data.

A first aspect of the present invention is a transmitting apparatus, comprising a transmitting means for transmitting the same contents of update information a plurality number of times, the update information representing that data has been updated, wherein the transmission timing of the same contents of the update information transmitted by the transmitting means is designated corresponding to operating state information of receiving means that receives the update information from the transmitting means.

A second aspect of the present invention is a transmitting method, comprising the step of a transmitting the same contents of update information a plurality number of times, the update information representing that data has been updated, wherein the transmission timing of the same contents of the update information transmitted at the transmitting step is designated corresponding to operating state information of receiving means that receives the update information from the transmitting means.

A third aspect of the present invention is a receiving apparatus for receiving a hierarchical

structure of a directory for hierarchically managing
the locations of contents data that is transmitted,
comprising a receiving means for receiving first
difference information, second difference information,
5 and third difference information, the first difference
information being obtained by detecting a change of
container entries, the second difference information
being obtained by detecting a change of leaf entries,
the directory being composed of container entries and
10 leaf entries, a container entry containing information
in the immediately lower hierarchical level thereof, a
leaf entry not containing information in the
immediately lower hierarchical level thereof, the third
difference information being transmitted at a
15 predetermined time period, the third difference
information being capable of reproducing the
hierarchical structure of the directory, and a managing
means for managing the hierarchical structure of the
directory formed corresponding to the first difference
20 information, the second difference information, and the
third difference information received by the receiving
means, wherein local operating state information of the
receiving apparatus is monitored and transmitted.

A fourth aspect of the present invention is a
25 receiving method for receiving a hierarchical structure
of a directory for hierarchically managing the
locations of contents data that is transmitted,

comprising the steps of receiving first difference
information, second difference information, and third
difference information, the first difference
information being obtained by detecting a change of
5 container entries, the second difference information
being obtained by detecting a change of leaf entries,
the directory being composed of container entries and
leaf entries, a container entry containing information
in the immediately lower hierarchical level thereof, a
10 leaf entry not containing information in the
immediately lower hierarchical level thereof, the third
difference information being transmitted at a
predetermined time period, the third difference
information being capable of reproducing the
15 hierarchical structure of the directory, and managing
the hierarchical structure of the directory formed
corresponding to the first difference information, the
second difference information, and the third difference
information received at the receiving step, wherein
20 local operating state information of the receiving
apparatus is monitored and transmitted.

A fifth aspect of the present invention is a
transmitting and receiving system, comprising a
transmitting means for transmitting the same contents
25 of update information a plurality number of times, the
update information representing that data has been
updated, and a receiving means for receiving the update

information transmitted by the transmitting means,
wherein the transmission timing of the same contents of
the update information transmitted by the transmitting
means is designated corresponding to operating state
5 information of the receiving means.

A sixth aspect of the present invention is a
transmitting and receiving method, comprising the step
of transmitting the same contents of update information
a plurality number of times, the update information
10 representing that data has been updated, and receiving
the update information transmitted at the transmitting
step, wherein the transmission timing of the same
contents of the update information transmitted at the
transmitting step is designated corresponding to
15 operating state information received at the receiving
step.

As was described above, according to the
first aspect and the second aspect of the present
invention, the same contents of update information is
20 transmitted a plurality number of times, the update
information representing that data has been updated.
The transmission timing of the same contents of the
transmitted update information is designated
corresponding to operating state information of a
25 receiving means. Thus, the reception probability of
which the receiving side receives update information is
high.

According to the third aspect and the fourth aspect of the present invention, first difference information, second difference information, and third difference information are received. The first difference information is obtained by detecting a change of container entries. The second difference information is obtained by detecting a change of leaf entries. The directory is composed of container entries and leaf entries. A container entry contains information in the immediately lower hierarchical level thereof. A leaf entry does not contain information in the immediately lower hierarchical level thereof. The third difference information is transmitted at a predetermined time period. The third difference information can be used to reproduce the hierarchical structure of the directory. The hierarchical structure of the directory formed is managed corresponding to the first difference information, the second difference information, and the third difference information that have been received. Local operating state information of the receiving apparatus is monitored and transmitted. Thus, the operating state information can be affected to the third difference information transmitted by the transmitting side at the intervals of the predetermined time period,

According to the fifth aspect and the sixth aspect of the present invention, the transmitting side

transmits the same contents of update information a plurality number of times, the update information representing that data has been updated. The receiving side receives the update information that has been transmitted. The transmission timing of the same contents of the update information that is transmitted is designated corresponding to operating state information on the receiving side. Thus, the update information is transmitted corresponding to the operating state of the receiving side.

These and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description of a best mode embodiment thereof, as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic diagram showing an example of which a receiver side cannot receive difference update data from a directory server for a predetermined time period;

Fig. 2 is a schematic diagram showing a system according to the present invention;

Fig. 3 is a schematic diagram for explaining a system of which a plurality of receiving sides are connected to a broadcasting network;

Fig. 4 is a schematic diagram for explaining a directory structure;

Fig. 5 is a schematic diagram showing an example of the structure of a container entry;

Figs. 6A and 6B are schematic diagrams showing an example of the structure of a leaf entry;

Fig. 7 is a functional block diagram for explaining the function of a transmitting side replicater;

Fig. 8 is a functional block diagram for explaining the function of a receiving side client;

Fig. 9 is a functional block diagram for explaining the function of a receiving side server;

Figs. 10A, 10B, 10C, 10D, 10E, and 10F are schematic diagrams for explaining difference update information of a directory structure;

Figs. 11A, 11B, 11C, and 11D are schematic diagrams for explaining difference update information of a directory structure;

Fig. 12 is a schematic diagram for explaining overall structure information of a directory structure;

Fig. 13 is a schematic diagram for explaining overall structure information of a directory structure;

Fig. 14 is a flow chart for explaining a synchronization managing method of container entries;

Figs. 15A and 15B are flow charts for explaining the synchronization managing method of the container entries in detail;

Fig. 16 is a flow chart for explaining the

synchronization managing method of the container entries in detail;

Fig. 17 is a flow chart for explaining a synchronization managing method of leaf entries;

5 Figs. 18A and 18B are flow charts for explaining the synchronization managing method of the leaf entries in detail;

10 Fig. 19 is a flow chart for explaining the synchronization managing method of the leaf entries in detail;

Figs. 20A, 20B, 20C, and 20D are schematic diagrams for explaining a bit arrangement structure of mask values of filtering masks;

15 Fig. 21 is a flow chart showing a mask value assigning process corresponding to the increase/decrease of a container entry in the case that an entry is added or deleted;

Figs. 22A and 22B are schematic diagrams for explaining a container entry mask scheme that is coded;

20 Figs. 23A and 23B are schematic diagrams for explaining a target mask list;

Fig. 24 is a flow chart showing a process for generating a target mask list;

25 Fig. 25 is a flow chart showing a process for selectively receiving broadcast leaf update information Msg.x1' corresponding to a target mask list;

Fig. 26 is a flow chart showing an example of

a process for setting a value of an overall structure information notification interval timer; and

Fig. 27 is a schematic diagram showing the result of an example of a statistic process for an operating ratio on the receiving side.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Next, with reference to the accompanying drawings, an embodiment of the present invention will be described. Fig. 2 shows an example of the structure of a system according to the present invention. A transmitting side 1 arranges many contents data distributed on a network such as the Internet or a broadcast network in a tree shape hierarchical structure and manages it as a directory structure. The transmitting side 1 transmits directory information that represents the directory structure to a broadcasting network 2. As shown in Fig. 3, many receiving devices on the receiving side 3 are connected to the broadcast network 2. The receiving side 3 can receive broadcast programs through the broadcasting network 2. The receiving side 3 receives directory information that is broadcast on the broadcasting network 2. With reference to the received directory information, a receiving side replicater 17 (that will be described later) on the receiving side 3 can select required information title from many information titles distributed on the broadcasting network 2 and other

networks and obtain the selected information title.

The transmitting side 1 and receiving side 3 are connected to each other through a bidirectional network 4. As shown in Fig. 3, many receiving devices on the receiving side 3 are connected to the bidirectional network 4 so that the receiving side devices bidirectionally communicate with the transmitting side 1.

As shown in Fig. 2, the transmitting side 1 comprises a transmitting side directory service client 10 (hereinafter referred to as transmitting side client 10), a transmitting side directory server 11 (hereinafter referred to as transmitting side server 11), and a transmitting side directory server replicater 12 (hereinafter referred to as transmitting side replicater 12). The transmitting side client 10, the transmitting side server 11, and the transmitting side replicater 12 are connected with a network such as the Internet so that they communicate with each other.

The transmitting side client 10 is a contents data provider that provides the user with contents data through a network (not shown). The transmitting side client 10 changes and updates the directory structure. The transmitting side client 10 may be disposed at any location of the network. The transmitting side server 11 inquires and changes the contents of the transmitting side client 10 and manages the directory

structure. Many transmitting side servers 11 may be distributed on the network. The transmitting side replicater 12 monitors the directory structure managed by the transmitting side server 11 and detects an
5 update of the directory structure. The transmitting side replicater 12 compares the pre-updated directory structure with the post-updated directory structure corresponding to the detected result, extracts the difference thereof, and generates the difference update
10 information of the directory structure. The structure of the difference update information will be described later.

The difference update information is periodically transmitted to the broadcasting network 2.
15 In addition, according to the present invention, the overall information of the directory structure managed by the transmitting side server 11 is transmitted to the broadcasting network 2 (hereinafter, this overall information is referred to as overall structure
20 information). As will be described later, the transmission intervals of the difference update information and those of the overall structure information are separately set. The receiving side 3 forms a local directory structure corresponding to the
25 received difference update information and overall structure information.

The receiving side 3 comprises a receiving

side directory server replicater 17 (hereinafter referred to as receiving side replicater 17), a receiving side directory server 16 (hereinafter referred to as receiving side server 16), and a receiving side directory service client 15 (hereinafter referred to as receiving side client 15). The receiving side 3 is for example a personal computer, an STB, or an IRD (as were described in the section of "Description of the Related Art"). The receiving side client 15 is for example application software such as WWW (World Wide Web) browser that accesses a directory structure and obtains and displays a plurality of different formats of data. The receiving side server 16 is for example a local database that stores directory information.

The overall structure information, the update information of the directory structure, and the difference information of the update information that are transmitted through the broadcasting network 2 are received by the receiving side replicater 17. The receiving side replicater 17 updates the local database stored in the receiving side server 16 corresponding to the received information and reforms the directory structure. Corresponding to a user's request or the like, the receiving side client 15 requests the receiving side replicater 17 for desired information. Corresponding to the request, the receiving side

replicater 17 searches the database of the receiving side server 16 and returns an address of the required information to the receiving side client 15.

Corresponding to the returned address, the receiving side client 15 can access information distributed on the network (not shown).

On the other hand, the transmitting side replicater 12 and the receiving side replicater 17 are connected to each other with the bidirectional network 4. Many receiving side replicaters 17 are connected to the bidirectional network 4. At least one receiving side replicater 17 bidirectionally communicates with the transmitting side replicater 12 through the bidirectional network 4.

Next, with reference to Fig. 4, the directory structure will be described. As shown in Fig. 4, the directory is hierarchically structured in a tree shape. Each node of the tree is referred to as entry. Each entry contains information. There are three types of entries that are one root entry, a plurality of container entries, and a plurality of leaf entries. A container entry can contain an entry in the immediately lower hierarchical level thereof. A hierarchy formed with container entries is hereinafter referred to as container hierarchy.

Entries other than the root entry and container entries are referred to as leaf entries. A

leaf entry cannot contain an entry in the immediately lower hierarchical level thereof. Thus, a leaf entry is a terminal node that cannot contain an entry. A hierarchy of a leaf entry is hereinafter referred to as leaf hierarchy. A leaf hierarchy is contained in a container entry.

An entry in the highest hierarchical level of the directory tree is referred to as root entry. The root entry represents the entire world of the directory structure. In the following description, it is assumed that a container entry contains at least one leaf entry or at least one container entry.

Each entry has a plurality of attributes. A name that is uniquely identified in the directory tree is referred to as entry name. With an entry name, the location of the entry in the directory structure can be designated. In the example shown in Fig. 4, the root entry is assigned an entry name A. A leaf entry in the immediately lower hierarchical level of the root entry (an entry at the lower left position of the root entry) is assigned an entry name A.B. A container entry in the immediately lower hierarchical level (an entry at the lower right position of the root direction) is assigned an entry name A.C. Each entry is assigned an entry name with periods corresponding to lower hierarchical levels routed from the root entry.

Fig. 5 shows an example of the structure of a

container entry. A container entry has attributes thereof, a list of container entries in the immediately lower hierarchical level of the current container entry, and a list of leaf entries in the immediately lower hierarchical level of the current container entry. The list of entries in the immediately lower hierarchical level of the current container entry may not contain elements. The number of attributes of the current container entry may be two or more as shown in Fig. 5.

Figs. 6A and 6B show an example of the structure of a leaf entry. As shown in Fig. 6A, a leaf entry has a plurality of attributes. Fig. 6B shows a real example of attributes of a leaf entry. Each attribute is composed of an attribute name and an attribute value. When a leaf entry is search information of contents data, one attribute name is an address. The attribute value is address information of contents data such as URL (Uniform Resource Locator).

The directory structure has container entries arranged in a tree shape corresponding to information genres under the root entry that represents the entire world.

Next, the structure of the transmitting side 1 will be described in detail. The transmitting side server 11 manages the directory structure as with the structure shown in Figs. 4, 5, 6A, and 6B. The

transmitting side client 10 changes the directory structure managed by the transmitting side server 11 corresponding to contents data that the transmitting side client 10 provides. A change of contents data of the transmitting side server 11 is monitored by the transmitting side replicater 12.

Fig. 7 is a functional block diagram for explaining the function of the transmitting side replicater 12. The transmitting side replicater 12 can be composed of for example a conventional computer system. The transmitting side replicater 12 comprises a CPU (Central Processing Unit), recording and storing mediums (such as a memory and a hard disk), a communicating means, and a user interface. The functional block shown in Fig. 7 is accomplished by application software that runs on the CPU. Each module shown in Fig. 7 is a functional element of the application software.

The transmitting side replicater 12 comprises an update detecting module 20, a message generating module 21, and a message broadcasting module 22. Each of the update detecting module 20, the message generating module 21, and the message broadcasting module 22 has a module that performs a process for a container hierarchy and a module that performs a process for a leaf hierarchy.

The update detecting module 20 is a module

that references the transmitting side server 11 and detects whether or not the directory structure managed by the transmitting side server 11 has been changed. The update detecting module 20 is composed of a
5 container hierarchy update detecting module 23 and a leaf hierarchy update detecting module 24. The container hierarchy update detecting module 23 monitors the transmitting side server 11 and detects whether or not the structure of the container hierarchy has been
10 changed. The leaf hierarchy update detecting module 24 monitors the transmitting side server 11 and detects whether the structure of the leaf hierarchy and the contents of the leaf entry have been changed.

The message generating module 21 is a module
15 that generates a message that represents difference update information of the directory structure corresponding to the detected result of the change of the directory structure by the update detecting module 20. The message generating module 21 is composed of a
20 container structure update message generating module 25 and a leaf entry update message generating module 26. The container structure update message generating module 25 generates a message that represents
25 difference update information of the structure change of the container hierarchy corresponding to the detected result of the container hierarchy update detecting module 23. The leaf entry update message

generating module 26 generates a message that represents update information of the leaf hierarchy corresponding to the detected result of the leaf hierarchy update detecting module 24.

5 The message broadcasting module 22 is a module that broadcasts the message generated by the message generating module 21 to the broadcasting network 2. The message broadcasting module 22 is composed of a container structure update message
10 broadcasting module 27 and a leaf entry update message broadcasting module 28. The container structure update message broadcasting module 27 broadcasts the message generated by the container structure update message
15 generating module 25. The leaf entry update message broadcasting module 28 broadcasts the message generated by the leaf entry update message generating module 26. The message broadcasting module 22 cyclically broadcasts the same message to the broadcasting network 2 a predetermined number of times.

20 Next, the structure of the receiving side 3 will be described in more reality. Fig. 8 is a functional block diagram for explaining the function of the receiving side client 15. The receiving side
25 client 15 can be composed of a conventional computer system. The receiving side client 15 comprises a CPU (Central Processing Unit), recording and storing mediums (such as a memory and a hard disk), a

communicating means, and a user interface. The functional block shown in Fig. 8 is accomplished by application software that runs on the CPU. Each module is a functional element of the application software.

5 As was described above, the receiving side client 15 is for example a WWW browser. The receiving side client 15 can integrally display and reproduce supplied contents data (for example still picture data, text data, audio data, and moving picture data). In addition, corresponding to a user's request that is input with a predetermined inputting means, the receiving side client 15 can control the displaying operation and the reproducing operation of such data.

10 The receiving side client 15 comprises a directory searching module 30, a user interactive managing module 31, and a contents data obtaining module 32. A user interface 33 is connected to the user interactive managing module 31. The user interface 33 is composed of a text inputting means (such as a keyboard), a pointing device (such as a mouse), and a displaying device. A contents data search request to the receiving side client 15 is interactively performed with the user interactive managing module 31 through the user interface 33.

20 When a contents data search request is input to the user interactive managing module 31, the user interactive managing module 31 requests the directory

searching module 30 for a directory entry corresponding to the desired contents data so as to search the address of the desired contents data. Corresponding to the search request, the directory searching module 30 transmits a directory entry search request to the receiving side server 16.

The search result of the directory entry corresponding to the search request is returned from the receiving side server 16 to the directory searching module 30. The search result is further returned from the directory searching module 30 to the user interactive managing module 31. When the directory entry information of the search result represents that the search result is a leaf entry, the address information of the contents data is extracted as one attribute. The user interactive managing module 31 transmits a contents data obtaining request to the contents data obtaining module 32 so as to obtain contents data corresponding to the extracted address information.

Corresponding to the received contents data obtaining request, the contents data obtaining module 32 transmits a contents data obtaining request to a contents data server 35. The contents data server 35 is a server connected to the receiving side client 15 through a bidirectional network 36 such as the Internet. The contents data server 35 provides the

user with contents data. The contents data may be provided through the bidirectional network 36 or the broadcasting network 2.

The contents data obtained from the contents data server 35 corresponding to the contents data obtaining request is supplied to the contents data obtaining module 32 through for example the bidirectional network 36. The contents data is returned from the contents data obtaining module 32 to the user interactive managing module 31. The user interactive managing module 31 outputs the received contents data to the user interface 33.

When the requested contents data is transmitted through the broadcasting network 2, the contents data obtaining module 32 may directly obtain desired contents data that is broadcast through the broadcasting network 2 corresponding to the contents data obtaining request.

Fig. 9 is a functional block diagram for explaining the function of the receiving side server 16. As with the receiving side client 15, the receiving side server 16 is composed of a conventional computer system. The receiving side server 16 comprises a directory update request processing module 40, a directory database 41, and a directory search request processing module 42.

The directory database 41 stores directory

information corresponding to the directory structure managed by the transmitting side server 11. As was described above, the receiving side replicater 17 receives difference update information of the directory structure from the transmitting side 1 through the broadcasting network 2. Although details will be described later, the receiving side replicater 17 transmits a request to the directory update request processing module 40 so as to update the directory information stored in the directory database 41 corresponding to the difference update information. Corresponding to the request, the directory update request processing module 40 updates the directory information stored in the directory database 41 with the difference update information.

On the other hand, the search request for the directory entry transmitted from the receiving side client 15 is received by the directory search request processing module 42. The directory search request processing module 42 searches the directory database 41 for the required directory entry corresponding to the received search request. The directory entry as the search result (for example, address information of a leaf entry) is returned from the directory search request processing module 42 to the receiving side client 15.

Since the system is structured as described

above, the user can search directory information with the receiving side client 15 and obtain address information with desired contents data as the search result. The user can obtain desired contents data corresponding to the obtained address information. The directory structure is monitored by the transmitting side replicater 12. The difference update information and the overall structure information of the directory structure are transmitted at intervals of a predetermined time period and supplied to the receiving side replicater 17 through the broadcasting network 2. Corresponding to the supplied difference update information and overall structure information, the receiving side replicater 17 on the user side updates the directory information stored in the directory database 41. Thus, the user can always have directory information that synchronizes with a real directory structure in the directory database 41.

Next, with reference to Figs. 10A, 10B, 10C, 10D, 10E, 10F, 11A, 11B, 11C, 11D, 12, and 13, the difference update information and the overall structure information of the directory structure will be described. In the following description, a process for adding or deleting a container entry C or a leaf entry 1 to/from the immediately lower hierarchical level of a container entry X of a particular container hierarchy designated by a schema version Sv is expressed as

follows.

(Sv, X, [+/-] [C/l])

The expression of the process for the directory structure represents the difference between the pre-processed directory structure and the post-processed directory structure. The expression can be used as difference update information.

On the other hand, the overall structure information is information that represents a directory structure at a particular time point. Assuming that the overall structure information is the difference to the root entry, the overall structure information can be represented with the above-described difference update information.

The schema version Sv is a value that changes corresponding to the change of the directory structure. The container entry X (or C) is a container entry name. In this example, a container entry name is represented by a uppercase alphabet character. The leaf entry 1 represents a leaf entry name. In this example, a leaf entry name is represented by a lowercase alphabet character. An addition of an entry is represented by [+]. A deletion of an entry is represented by [-]. A slash mark in parentheses [] represents that one of two characters therein is placed. In Figs. 10A to 10F and 11A to 11D, a concentric square represents a container entry, whereas a single square represents a leaf entry.

In Figs. 10A to 10F and 11A to 11D, the root entry is not shown except for a connection line thereof.

Fig. 10A shows a directory structure 100 of which only a container entry A is disposed in the immediately lower hierarchical level of the root entry (not shown). This state is referred to as schema version $S_v = 1$. In this state, a process of (1, A, +B) is performed. In other words, a container entry B is added to the immediately lower hierarchical level of the container entry A. Thus, a directory structure 101 as shown in Fig. 10B is generated. Since the container entry B is added to the state shown in Fig. 10A, since a hierarchical image of the container entries is changed, the schema version is changed to $S_v = 2$.

In the state shown in Fig. 10B, a process of (2, A, +a) is performed. In other words, a leaf entry a is added to the immediately lower hierarchical level of the container entry A. Thus, a directory structure 102 shown in Fig. 10C is generated. In addition, a process of (2, A, -a) is performed in the state shown in Fig. 10C. In other words, the leaf entry a is deleted from the immediately lower hierarchical level of the container entry A. Thus, a directory structure 103 as shown in Fig. 10D is generated. Thereafter, a process of (2, A, -B) is performed in the state shown in Fig. 10D. In other words, the container entry B is deleted from the immediately lower hierarchical level

of the container entry A. Thus, a directory structure 104 shown in Fig. 10E is generated.

In the state shown in Fig. 10E, since the hierarchical image of the container entry has been changed from the state shown in Fig. 10D, the schema version Sv is updated. Thus, the schema version is changed to Sv = 3. Consequently, in the state shown in Fig. 10E, a process for adding a container entry C to the immediately lower hierarchical level of the container entry A is expressed by (3, A, +C). When this process is performed, a directory structure 105 shown in Fig. 10F is generated.

In the example shown in Figs. 10A to 10F, (1, A, +B), (2, A, +a), (2, A, -a), (2, A, -B), and (3, A, +C) are difference update information in individual states.

Figs. 11A, 11B, 11C, and 11D show another example of which a directory structure is changed. In the example shown in Figs. 10A to 10F, one process is performed at a time. However, in Figs. 11A to 11D, two processes are performed at a time. Fig. 11A shows a directory structure 106 of which only a container entry A is disposed in the immediately lower hierarchical level of the root entry (not shown). This state is referred to as schema version Sv = 1. In the state shown in Fig. 11A, processes of (1, A, +B) and (1, A, +a) are successively performed. In other words, a

container entry B and a leaf entry a are added in the immediately lower hierarchical level of the container entry A. Thus, a directory structure 107 shown in Fig. 11B is generated. In this state, the hierarchical image of the container entries is changed. Thus, the schema version is changed to Sv = 2.

In the state shown in Fig. 11B, two processes of (2, A, -a) and (2, B, +b) are successively performed. In other words, a leaf entry a is deleted from the immediately lower hierarchical level of the container entry A. Thereafter, a leaf entry b is added to the immediately lower hierarchical level of the container entry B. Thus, a directory structure 108 shown in Fig. 11C is generated.

In the state shown in Fig. 11C, two processes of (2, B, +C) and (2, C, +c) are performed. In other words, a container entry C is added to the immediately lower hierarchical level of the container entry B. Thereafter, a leaf entry c is added to the immediately lower hierarchical level of the container entry C. In this case, since a leaf entry is added to an added container entry, the order of the processes cannot be changed. Thereafter, a directory structure 109 shown in Fig. 11D is generated. Since the hierarchical image of the container entry is changed, the schema version Sv is updated. Thus, the schema version is changed to Sv = 3.

In the example shown in Figs. 11A to 11D, (1, A, +B) and (1, A, +a), (2, A, -a) and (2, B, +b), and (2, B, +C) and (2, C, +c) are difference update information in individual stages. As was described above, when a plurality of processes are performed as one updating process of a directory structure, the order of processes should be considered.

Fig. 12 shows overall structure information corresponding to difference update information shown in Figs. 10A to 10F. The overall structure information is transmitted from the transmitting side replicator 12 at intervals of a predetermined time period T. In the following description, the time period T in which the overall structure information is transmitted is referred to as overall structure information notification period T. In Fig. 12, it is assumed that time passes from the left side to the right side. In addition, it is assumed that the intervals of changes of the directory structure (namely, structures 100, 101, 102, 103, and 104) are constant. In this example, the overall structure information notification period T corresponds to the interval of the structures 100 to 102 and the interval of the structures 102 to 104.

As was described above, in this example, the overall structure information is represented as difference information from the root entry to a directory structure at a particular time point. Thus,

as shown in Fig. 12, the overall structure information corresponding to the structure 102 can be expressed as (0, root, +A), (0, A, +B), and (0, A, +a) in the order of the processes. In other words, the individual processes are performed to the root entry in such an order. Individual entries are added and thereby the structure 102 is expressed. Likewise, in the structure 104, only the container entry A is disposed in the immediately lower hierarchical level of the root entry. Thus, the overall structure information at the time point corresponding to the structure 104 is expressed as (0, root, +A).

In the overall structure information notification period T, the schema version Sv is reset to 0. Thus, Sv in the overall structure information is always 0.

Fig. 13 shows overall structure information corresponding to the structures shown in Figs. 11A to 11D. In this example, the interval of the structures 106 to 109 corresponds to the overall structure information notification period T'. The overall structure information corresponding to the structure 109 can be represented by (0, root, +A), (0, A, +B), (0, B, +b), (0, B, +C), and (0, C, +c) in the order of processes.

The difference update information and the overall structure information of the directory

structure are not limited to the above-described examples. Instead, they may be changed corresponding to the applied system.

The contents of a leaf entry may be modified along with a deletion and an addition thereof from/to the immediately lower hierarchical level of a container entry. When the contents of a leaf entry are modified, the directory structure is not changed. In this case, difference update information is generated with for example a leaf entry name and a sequence of attribute names and attribute values that were modified. In this case, the difference update information is expressed as follow.

```
{  
    LeafEntryName,  
    Set of {AttributeName, AttributeValue}  
}
```

In the system according to the present invention, as was described above, difference update information and overall structure information are unidirectionally transmitted from the transmitting side 1 to the receiving side 3 through the broadcasting network 2. In addition, there are many receiving devices on the receiving side 3 against one transmitting side 1. In addition, the operating states of the individual receiving devices on the receiving side 3 differ. Thus, it is necessary to synchronize

directory information managed on the transmitting side 1 with directory information managed on the receiving side 3.

5 Next, a method for synchronizing directory information stored in the transmitting side server 11 on the transmitting side 1 with directory information stored in the receiving side server 16 on the receiving side 3 and managing the synchronization of the directory structure will be described.

10 First, with reference to Fig. 14, a method for managing the synchronization of container entries will be described. At step S1, the transmitting side client 10 changes the structure of the container hierarchy of a directory structure managed by the
15 transmitting side server 11. For example, the transmitting side client 10 performs a process for adding a new container entry and/or a leaf entry to the immediately lower hierarchical level of a particular container entry and a process for deleting a container
20 entry and/or a leaf entry from the immediately lower hierarchical level of a particular container entry.

25 At step S2, the transmitting side replicater 12 detects a change performed in the transmitting side server 11. Corresponding to the detected result, the transmitting side replicater 12 generates container structure update information Msg.1 corresponding to the change of the container hierarchical structure. The

generated container structure update information Msg.1 is broadcast to the broadcasting network 2. The same contents of the container structure update information Msg.1 are cyclically broadcast a predetermined number of times.

At step S3, the container structure update information Msg.1 that has been broadcast is received by the receiving side replicater 17. The receiving side replicater 17 changes the container hierarchy structure managed with directory information stored in the receiving side server 16 corresponding to the received container structure update information Msg.1. Thus, the structure of the container hierarchy of the directory information on the transmitting side 1 is synchronized with that on the receiving side 3.

The format of the container structure update information Msg.1 is expressed as follows.

```
Container Structure Update Message {  
    MessageID,  
    Difference update information  
}
```

"MessageID" is identification information of the message (container structure update information Msg.1). For example, the "Message ID" is an integer that is incremented by 1 whenever a message is generated. "Difference update information" is difference update information of the above described directory structure

corresponding to a change of the container hierarchy structure.

The process performed at step S2 of the flow chart shown in Fig. 14 will be described in detail with reference to a flow chart shown in Figs. 15A and 15B. All the process of the flow chart shown in Figs. 15A and 15B is performed by the transmitting side replicater 12. At step S100, an overall structure information notification period timer T_1 that counts the overall structure information notification period T is set to a multiple of a time period of a timer T_2 that is set at step S102. Thereafter, the overall structure information notification period timer T_1 is started. The detailed setting method of the overall structure information notification period timer T_1 will be described later.

After the overall structure information notification period timer T_1 is set, the flow advances to step S101. At step S101, all information of the hierarchical structure of the container entries of the transmitting side server 11 is read. The information of the hierarchical structure of the container entries is stored as a copy 1 to the recording medium or the storing medium such as a memory or a hard disk of the transmitting side replicater 12.

After the copy 1 is stored, the flow advances to step S102. At step S102, the timer T_2 is set to a

predetermined time period. Thereafter, the timer T_2 is started. Thereafter, the flow advances to step S103.

At step S103, the overall structure information notification period timer T_1 and the timer T_2 count
5 respective set time periods. When one of the time periods that has been set to the overall structure information notification period timer T_1 and the timer T_2 elapses, the flow advances to step S104.

At step S104, it is determined whether or not
10 the predetermined time period of the overall structure information notification period timer T_1 has elapsed. When the determined result at step S104 is No (namely, the time period that had been set to the timer T_2 has elapsed), the flow advances to step S106.

On the other hand, when the determined result
15 at step S104 is Yes (namely, the time period that had been set to the overall structure information notification period timer T_1 has elapsed), the flow advances to step S105. At step S105, the contents of
20 the copy 1 stored at step S101 are cleared. Thus, the contents of the copy 1 are only the root entry. Thereafter, the flow advances to step S106.

At step S106, all information of the
25 hierarchical structure of the container entries of the transmitting side server 11 is read. The hierarchical structure of the container entries that are read is stored as a copy 2 to the recording medium or the

storing medium such as a memory or a hard disk of the transmitting side replicater 12.

At step S107, the copy 1 is compared with the copy 2 stored at step S106. Thereafter, the flow advances to step S108. At step S108, it is determined whether there is a difference between the copy 1 and the copy 2. When the determined result at step S108 is No (namely, there is no difference between the copy 1 and the copy 2), the flow returns to step S100. At step S100, the overall structure information notification period timer T_1 is set and the process after step S100 is repeated.

In the case that the time period that had been set to the overall structure information notification period timer T_1 has elapsed (the determined result at step S104 is Yes) and the contents of the copy 1 has been cleared at step S105, the copy 1 is compared with the copy 2 at step S107. Thus, the difference of the hierarchical structure of the container entries stored as the copy 2 against the root entry is obtained.

On the other hand, when the determined result at step S108 is Yes (namely, there is a difference between the copy 1 and the copy 2), the flow advances to step S109. At step S109, corresponding to the difference between the copy 1 and the copy 2, difference update information is generated. Thus,

container structure update information Msg.1 containing the difference update information is generated. The container structure update information Msg.1 is transmitted to the broadcasting network 2. Thus, the container structure update information Msg.1 is broadcast through the broadcasting network 2. The broadcast container structure update information Msg.1 is received by the receiving side replicater 17.

When the container structure update information Msg.1 is broadcast at step S109, the flow advances to step S110. At step S110, the contents of the copy 1 are substituted with the contents of the copy 2. Thereafter, the flow returns to step S100.

Next, the process of step S3 of the flow chart shown in Fig. 14 will be described in detail with reference to a flow chart shown in Fig. 16. All the process of the flow chart shown in Fig. 16 is performed by the receiving side replicater 17. At step S20, the container structure update information Msg.1 that has been broadcast through the broadcasting network 2 by the transmitting side replicater 12 is received by the receiving side replicater 17.

At step S21, it is determined whether or not the container structure update information Msg.1 has been received first time at step S20. When the determined result at step S21 is Yes (namely, the container structure update information Msg.1 has been

received first time), the flow advances to step S23.
At step S23, the message ID contained in the container
structure update information Msg.1 is stored as a copy
3 to the recording medium or the storing medium such as
5 a memory or a hard disk of the receiving side
replicater 17.

Thereafter, the flow advances to step S24.
At step S24, corresponding to the contents of the
received container structure update information Msg.1
10 (namely, the difference update information contained in
the container structure update information Msg.1), the
directory information managed by the receiving side
server 16 is updated. The structure of the container
hierarchy represented by the directory information is
15 changed. Thereafter, the flow returns to step S20.

On the other hand, when the determined result
at step S21 is No (namely, the container structure
update information Msg.1 has been received at step S20
not first time), the flow advances to step S22. At
20 step S22, it is determined whether or not the message
ID contained in the received container structure update
information Msg.1 is the same as the message ID stored
as the copy 3 at step S23. When the determined result
at step S22 is Yes (namely, they are the same), the
25 flow returns to step S20.

On the other hand, when the determined result
at step S22 is No (namely, they are not the same), the

flow advances to step S23. At step S23, as was described above, the message ID is stored as the copy 3 to the storing medium. In this case, the message ID that has been received and stored is overwritten with the message ID that has been newly received.

Thereafter, the flow advances to step S24. At step S24, corresponding to the received container structure update information Msg.1, the contents of the container entry hierarchy of the receiving side server 16 are changed.

Next, with reference to a flow chart shown in Fig. 17, a method for managing the synchronization of leaf entries will be described. At step S30, the transmitting side client 10 changes a leaf entry in the immediately lower hierarchical level of a particular container entry of a directory structure managed by the transmitting side server 11. For example, the transmitting side client 10 performs a process for adding a new leaf entry to the immediately lower hierarchical level of a particular container entry, a process for deleting a leaf entry from the immediately lower hierarchical level of a particular container entry, or a process for modifying a leaf entry of the immediately lower hierarchical level of a particular container entry.

At step S31, the transmitting side replicater 12 detects a change of a leaf entry in the immediately

lower hierarchical level of a particular container entry of the transmitting side server 11.

Corresponding to the detected result, leaf update information Msg.x1 due to the change of the leaf entry in the immediately lower hierarchical level of the particular container entry is generated. The generated leaf update information Msg.x1 is cyclically broadcast to a plurality of receiving side replicaters 17 through the broadcasting network 2.

At step S32, the leaf update information Msg.x1 that has been broadcast is received by the receiving side replicaters 17. Each receiving side replicater 17 changes a relevant leaf entry managed with the directory information stored in the receiving side server 16 corresponding to the received leaf update information Msg.x1. Thus, a leaf entry of the directory information on the transmitting side 1 is synchronized with a leaf entry of the directory information on the receiving side 3.

The format of the leaf update information Msg.x1 is expressed as follows.

```
Leaf Entry Update Message {  
    MessageID,  
    Difference update information  
}
```

"MessageID" is identification information of the message (leaf update information Msg.x1). For example,

the "Message ID" is an integer that is incremented by 1 whenever a message is generated. "Difference update information" is difference update information of the above-described directory structure.

5 Next, the process of step S31 of the flow chart shown in Fig. 17 will be described in detail with reference to a flow chart shown in Figs. 18A and 18B. All the process of the flow chart shown in Fig. 17 is performed by the transmitting side replicater 12. The process of the flow chart shown in Figs. 18A and 18B is performed by the transmitting side replicater 12 for all container entries of the directory structure managed by the transmitting side server 11. At step S120, an overall structure information notification period timer T_1' that counts the overall structure information notification period T is set to a multiple of a time period of a timer T_2 that is set at step S122. Thereafter, the timer T_1 is started. As will be described later, different time periods can be set to the overall structure information notification period timer T_1' and the above-described overall structure information notification period timer T_1 .

20 After the timer T_1 is set, the flow advances to step S121. At step S121, leaf entry names in the immediately lower hierarchical level of a particular container entry (referred to as container entry A) of the transmitting side server 11 are read. The leaf

entry names that have been read are stored as a copy 4 to the recording medium or the storing medium such as a memory or a hard disk of the transmitting side replicater 12.

5 After the copy 4 is stored, the flow advances to step S122. At step S122, the timer T_2 is set to a predetermined time period. Thereafter, the flow advances to step S123. At step S123, the overall structure information notification period timer T_1' and the timer T_2 count the respective time periods that
10 have been set at step S120. Thereafter, the flow advances to step S124. At step S124, it is determined whether or not the time period that had been set to the overall structure information notification period timer
15 T_1 has elapsed.

 When the determined result at step S124 is No (namely, the time period that has been set to the timer T_2 has elapsed), the flow advances to step S126.

 On the other hand, when the determined result
20 at step S124 is Yes (namely, the time period that had been set to the overall structure information notification period timer T_1' has elapsed), the flow advances to step S125. At step S125, the contents of the copy 4 stored at step S121 are cleared. Since the
25 contents of the copy 4 are cleared, the copy 4 contains only the above-described container entry A. Thereafter, the flow advances to step S126.

At step S126, all leaf entry names in the immediately lower hierarchical level of a particular container entry (in this example, the container entry A) of the transmitting side server 11 are read. The leaf entry names that have been read are stored as a copy 5 to the recording medium or the storing medium such as a memory or a hard disk of the transmitting side replicater 12.

At step S127, the copy 4 is compared with the copy 5 stored at step S126. Thereafter, the flow advances to step S128. At step S128, it is determined whether or not there is a difference between the copy 4 and the copy 5. When the determined result at step S128 is No (namely, there is no difference), the flow returns to step S120. At step S120, the overall structure information notification period timer T_1 is set. Thereafter, the process after step S120 is repeated.

On the other hand, when the determined result at step S128 is Yes (namely, there is a difference between the copy 4 and the copy 5), the flow advances to step S129. At step S129, corresponding to the difference between the copy 4 and the copy 5, difference update information is generated. Thus, leaf update information Msg.x1 containing the difference update information is generated. The generated leaf update information Msg.x1 is transmitted to the

broadcasting network 2. The leaf update information
Msg.x1 is broadcast through the broadcasting network 2.
The broadcast leaf update information Msg.x1 is
received by a plurality of receiving side replicaters
17.

When the leaf update information Msg.x1 is
broadcast at step S129, the flow advances to step S130.
At step S130, the contents of the copy 4 are
overwritten with the contents of the copy 5.
Thereafter, the flow returns to step S120.

In the case that the time period that has
been set to the overall structure information
notification period timer T_1' has elapsed at step S124
and the contents of the copy 4 has been cleared at step
S125, corresponding to the difference update
information generated at step S129, a new leaf entry is
added to the container entry A of which information in
the immediately lower hierarchical level thereof has
been cleared.

Next, the process of step S32 of the flow
chart shown in Fig. 17 will be described in detail with
reference to a flow chart shown in Fig. 19. All the
process of the flow chart shown in Fig. 19 is performed
by the receiving side replicater 17. At step S50, leaf
update information Msg.x1 that has been broadcast by
the transmitting side replicater 12 through the
broadcasting network 2 is received by the receiving

side replicater 17.

At step S51, it is determined whether or not the leaf update information Msg.x1 has been received at step S50 first time. When the determined result at
5 step S51 is Yes (namely, the leaf update information Msg.x1 has been received first time), the flow advances to step S53. At step S53, the message ID of the received leaf update information Msg.x1 is stored as a copy 6 to the recording medium or the storing medium
10 such as a memory or a hard disk of the receiving side replicater 17.

Thereafter, the flow advances to step S54. At step S54, corresponding to the contents of the received leaf update information Msg.x1 (namely, the
15 difference update information contained in the leaf update information Msg.x1), a relevant leaf entry of the directory information managed by the receiving side server 16 is changed. Thereafter, the flow returns to step S50.

On the other hand, when the determined result at step S51 is No (namely, the leaf update information
20 Msg.x1 has been received not first time), the flow advances to step S52. At step S52, it is determined whether or not the message ID contained in the received
25 leaf update information Msg.x1 is the same as the message ID stored as the copy 6 at step S53. When the determined result at step S52 is Yes (namely, they are

the same), the flow returns to step S50.

On the other hand, when the determined result at step S52 is No (namely, they are not the same), the flow advances to step S53. At step S53, as was described above, the message ID is stored as a copy 6 to the storing medium. In this case, the message ID that has been received and stored is overwritten with the message ID that has been newly received.

Thereafter, the flow advances to step S54. At step S54, corresponding to the received leaf update information Msg.x1, a relevant left entry of the receiving side server 16 is changed.

At step S31 of the flow chart shown in Fig. 17, the leaf update information Msg.x1 for all the container entries of the directory structure managed by the transmitting side 1 is broadcast. Thus, it is supposed that the data amount of the leaf update information Msg.x1 is huge. Thus, as was described as a problem mentioned in the section of the related art reference, when the receiving side 3 receives all the leaf update information Msg.x1 and performs the process shown in Fig. 19 for it, the receiving side 3 is adversely loaded. To prevent that, the receiving side 3 should effectively filter only the leaf update information Msg.x1 of leaf entries in the immediately lower hierarchical level of container entries that are frequently inquired from that for all the container

entries that have been broadcast.

For example, it is assumed that the receiving side replicater 17 is used along with for example a set top box (STB) that is connected to a television

5 receiver or the like and that has a limited processing capability and storing capacity (in other words, the receiving side replicater 17 is used in an environment of an insufficient computer resource). In this case, the receiving data amount of the leaf update information Msg.x1 that is broadcast is limited. Thus, 10 it is necessary to select the received leaf update information Msg.x1 and supply the selected data to the receiving side replicater 17 so as to reduce the storage cost and the message processing cost. In other 15 words, the cost for storing and processing unnecessary data should be reduced. In particular, as the directory service is becoming common and the directory structure managed by the transmitting side server 11 is becoming huge, the selecting process for the leaf update information Msg.x1 is becoming important. 20

Next, the filtering process for the leaf update information Msg.x1 will be described. In addition, an effective filtering method according to the present invention will be described. The 25 transmitting side replicater 12 adds a filtering mask to leaf update information Msg.x1 to be broadcast. With the filtering mask, the receiving side replicater

17 performs a filtering process. A mask schema structure for interpreting a filtering mask and a method for causing the transmitting side replicater 12 to notify the receiving side replicater 17 of a mask schema structure will be described later.

The structure of a message (Msg.xl') of which a filtering mask has been added to leaf update information Msg.xl is defined as follows. The above-described leaf update information Msg.xl is substituted with the leaf update information Msg.xl'. In other words, the leaf update information Msg.xl' is defined as follows:

```
Leaf Entry Update Message {  
    MessageID,  
    FilteringMask,  
    Difference update information  
}
```

As with the above-described leaf update information Msg.xl, "MessageID" is an integer as identification information of the message (leaf update information Msg.xl'). For example, whenever a message is generated, the "MessageID" is incremented by 1. "Difference update information" is information that represents a process such as addition, deletion, or attribute change of a leaf entry in the immediately lower hierarchical level of a container entry designated by the filtering mask.

The structure of "FilteringMask" (filtering mask) is defined as follows.

```
FilteringMask {  
    MaskSchema Version,  
5    Mask Value  
}
```

"MaskSchema Version" is equivalent to a message ID of the above-described container structure update information Msg.1. Whenever a filtering mask is
10 generated, the "MaskSchema Version" is incremented by 1. "Mask Value" is the value of a mask represented as for example a bit string or on the order of bytes.

The structure of the mask value is defined by a mask schema corresponding to a mask schema version.
15 The mask schema will be described later. The transmitting side replicater 12 notifies the receiving side replicater 17 of the mask schema with another message that will be described later.

Next, the method for assigning a mask value
20 will be described. According to the embodiment, each of container entries in the immediately lower hierarchical level of a particular container entry is identified with a bit string composed of a predetermined number of bits. With reference to a mask
25 value contained in the received leaf update information Msg.x1', the receiving side replicater 17 performs a filtering process so as to selectively extract desired

leaf update information Msg.xl'.

The bit array structure of the mask value of a filtering mask is designated corresponding to the hierarchical structure of container entries. For example, as shown in Fig. 20A, corresponding to the assigning method for entry names described with reference to Fig. 4, to identify entries X.A, X.B, X.C, X.D, and X.E in the immediately lower hierarchical level of a particular container entry X, three-bit mask values (000), (001), (010), (011), and (100) are assigned. In Fig. 20, "... " represents that there is a container entry in the immediately higher hierarchical level of the current entry.

When an entry is added or deleted to/from a container entry in the immediately lower hierarchical level of a container entry X, a process of a flow chart shown in Fig. 21 is performed. A mask value is assigned corresponding to an addition or a deletion of a container entry. In the following description, a container hierarchy in the state before a container entry is added or deleted is referred to as pre-update container hierarchy. In this example, it is assumed that the number of mask digits M' of the pre-update container hierarchy has been stored in for example the memory of the transmitting side replicater 12.

At step S60, the transmitting side replicater 12 obtains the number of container entries N in the

immediately lower hierarchical level of a target container entry. With reference to the list of the container entries in the immediately lower hierarchical level of the target container entry, the number of container entries N is obtained. Thereafter, the flow advances to step S61. At step S61, the number of bits M that can uniquely identify N elements is selected. Thus, the number of mask digits is designated to M. In the example shown in Fig. 20A, since the container entry X has five container entries in the immediately lower hierarchical level thereof, [3] bits that can uniquely identify the five container entries are designated as the number of mask digits.

Thereafter, the flow advances to step S62. At step S62, it is determined whether or not the number of bits M designated at step S61 is the same as the number of mask digits M' designated to the pre-update container hierarchy. When the determined result at step S62 is Yes (namely, the number of mask digits M is the same as the number of mask digits M'), the flow advances to step S63.

At step S63, container entries of the post-update container hierarchy corresponding to those of the pre-update container hierarchy are designated the same mask value. Thereafter, the flow advances to step S64. At step S64, when there is a container entry of the pre-update container hierarchy that does not

correspond to that of the post-update container hierarchy, the container entry is assigned a unique mask value that is not used for mask values of the other container entries of the same container hierarchy.

On the other hand, when the determined result at step S62 is No (namely, the number of mask digits M is not the same as the number of mask digits M'), the flow advances to step S65. At step S65, unique mask values are assigned to all the container entries of the container hierarchy.

Now, consider that case that a new container entry "... X.F" is added to the state shown in Fig. 20A and thereby a container hierarchy shown in Fig. 20B is generated. In this case, since the number of container entries N in the immediately lower hierarchical level of the container entry " ... X" is 6. To uniquely identify the six container entries, three bits are required. Thus, the number of mask digits M of the container hierarchy in the immediately lower hierarchical level of the post-update container entry " ... X" is $M = 3$. Since the number of mask digits M' of the pre-update container hierarchy is $M' = 3$, the number of mask digits M' is the same as the number of mask digits M. Thus, mask values of entries of the pre-update container hierarchy are assigned to the container entries " ... X.A", "... X.B", "... X.C",

"... X.D", and "... X.E" shown in Fig. 20B (at step S63). On the other hand, the container entry "... X.F" that has been newly added is designated a unique mask value (101) that is different from other mask values of the other container entries of the same container hierarchy (at step S64).

Next, consider the case that the container entry "... X.C" is deleted from the state shown in Fig. 20A and thereby a container hierarchy shown in Fig. 20C is generated. In this case, the number of container entries N in the immediately lower hierarchical level of the container entry "... X" is $N = 4$. Thus, with two bits as the number of mask digits M, these container entries can be uniquely identified. Consequently, the number of mask digits M of the post-update container hierarchy is $M = 2$. On the other hand, the number of mask digits M' of the pre-update container hierarchy is $M' = 3$. Thus, the number of mask digits M' of the pre-update container hierarchy is not the same as the number of mask digits M of the post-update container hierarchy. In this case, the flow advances to step S65. At step S65, all the entries of the hierarchy are assigned new mask values with the number of mask digits $M = 2$.

Next, consider that case that a new container entry "... X.G" is added to the state shown in Fig. 20C and thereby a state shown in Fig. 20 is generated.

In this case, the number of container entries N in the immediately lower hierarchical level of the container entry "... X" is $N = 5$. To uniquely identify these container entries, the number of mask digits should be
5 $M = 3$. However, the number of mask digits M of the post-update container hierarchy is not the same as the number of mask digits M' of the pre-update container hierarchy. Thus, in this case, new mask values are assigned to all the container entries in the
10 immediately lower hierarchical level of the container entry "... X" at step S65.

Mask values are bit-assigned from the highest hierarchical level of the directory structure. On the other hand, according to the embodiment of the present
15 invention, as was described above, the number of mask digits depends on the number of entries of the same hierarchical level. In addition, when an entry is deleted or added, the number of entries of the container hierarchy changes. Thus, the number of mask
20 digits changes. Consequently, an information mechanism for determining the relation between bits of the bit string that represent mask values and container entries (or container hierarchy) and for interpreting mask values is required.

25 According to the embodiment of the present invention, a mask schema (MaskSchema) is defined as follows:

```

MaskSchema {
    MaskSchema Version,
    TotalMaskLength,
    Set of ContainerEntryMaskSchema
}

```

"MaskSchema Version" (mask schema version) is equivalent to the message ID of the above-described container structure update information Msg.1. Whenever a filtering mask is generated, the "MaskSchema Version" is incremented by 1. "TotalMaskLength" (total mask length) represents the total bit length of all mask values of the overall container hierarchy. In other words, the total mask length corresponds to the number of bits required to represent all hierarchical levels of the directory structure. "Set of ContainerEntryMaskSchema" (set of container entry mask schema) represents an array of "ContainerEntryMaskSchema" (container entry mask schema) that will be described later.

The above-described container entry schema defines a filtering mask corresponding to a particular container entry. In other words, the container entry mask schema is defined as follows:

```

ContainerEntryMaskSchema {
    ContainerEntryName,
    OffsetLength,
    MaskLength,
}

```

AssignedMaskValue

}

"ContainerEntryName" (container entry name) is a character string that represents the entry name of a target container entry. "OffsetLength" (offset length) is an offset value from the first bit of all mask values of a filtering mask of the container entry.

"MaskLength" (mask length) represents the number of digits (bit length) of a mask value.

"AssignedMaskValue" (assigned mask value) is a mask value as a bit string assigned to an object container entry.

Next, with reference to Figs. 22A and 22B, a container entry mask schema that is coded will be described. Fig. 22A corresponds to Fig. 20A. Referring to Fig. 22A, there are five container entries " ... X.A", " ... X.B", " ... X.C", " ... X.D", and " ... X.E" in the immediately lower hierarchical level of a particular container entry " ... X". Mask values with a mask length of three digits are assigned to the five container entries. In this example, it is assumed that these five container entries do not have other entries in the immediately lower hierarchical level thereof.

Fig. 22B shows an example of the mask value of a container entry " ... X.C". In this example, since the offset length is 77 bits, it is clear that

the mask value assigned to the container entry " ... X.C" with a mask length of three bits is three bits starting from 78-th bit of the mask value the container entry " ... X.C". The mask value of the 77 bits
5 contained in the offset length is an assigned mask value corresponding to a container entry in the immediately upper hierarchical level of the container entry " ... X.C".

10 In such a manner, the position of a mask value assigned to a target container entry is defined and a container entry mask schema is coded.

Next, a more practical example of a container entry mask schema will be described. A container entry mask schema corresponding to the above-described
15 container entry " ... X.C" is defined as follows:

```
ContainerEntryMaskSchema {  
    " ... X.C", (ContainerEntryName)  
    77, (OffsetLength)  
    3, (MaskLength)  
    010 (AssignedMaskValue)  
20  
}
```

Characters in parentheses are just for comments and omissible.

25 A container entry schema corresponding to the container entry " ... X.D" shown in Fig. 22A is for example defined as follows:

```
ContainerEntryMaskSchema {
```



```
" ... X.D",
```

```
77,
```

```
3,
```

```
011
```

```
5
```

```
}
```

Assuming that the mask schema version is 498
and that the total mask length is 134 bits, the mask
schema is defined as follows:

```
MaskSchema {
```

```
10
```

```
498, (MaskSchema Version)
```

```
134, (TotalMaskLength)
```

```
...
```

```
ContainerEntryMaskSchema {
```

```
" ... X.C",
```

```
15
```

```
77,
```

```
3,
```

```
010
```

```
}
```

```
ContainerEntryMaskSchema {
```

```
20
```

```
" .... X.D,
```

```
77,
```

```
3,
```

```
011
```

```
}
```

```
25
```

```
...
```

```
}
```

In the above example, the container entry mask schemas

of the container entries " ... X.C" and "... X.D" are contained in a mask schema. In reality, another container entry mask schema is contained in " ... ". As is clear from this example, a mask schema contains container entry mask schemas of all container entries of one directory structure.

In this example, although the total mask length is 134 bits, the offset value and the mask length of the container entry mask schema of the container entries " ... X.C" and " ... X.D" are 77 bits and 3 bits, respectively. Thus, the total bit length is 80 bits. This means that the container entries " ... X.C" and " ... X.D" contain lower container hierarchies.

The filtering mask corresponding to the container entry " ... X.C" of the above-described mask schema is coded as follows:

```
FilteringMask {  
    498, (MaskSchema Version)  
    ..... 010 (Mask Value)  
}
```

Mask values other than "011" are filled with bits of mask values assigned to container entries of other hierarchical levels.

Likewise, the filtering mask corresponding to the container entry " ... X.D" is coded as follows:

```
FilteringMask {
```

498, (MaskSchema Version)

..... 011 (Mask Value)

}

The transmitting side replicater 12 monitors
5 the transmitting side server 11, detects a change of
the hierarchical structure of container entries, and
changes the above-described mask schema. Thus, when
the receiving side 3 properly performs a filtering
process, the transmitting side replicater 12 should
10 notify the receiving side replicater 17 of the changed
mask schema along with difference update information
corresponding to the change of the hierarchical
structure.

According to the present invention, to allow
15 the transmitting side replicater 12 to notify the
receiving side replicater 17 of the mask schema, the
mask schema structure is added to the structure of the
above-described container structure update information
Msg.1. Container structure update information Msg.1'
20 to which a mask schema structure is added is defined as
follows:

```
Container Structure Update Message {  
    MessageID,  
    difference update information,  
25    MaskSchema  
}
```

Whenever the structure of the container hierarchy is

changed, the mask schema may be changed. Thus, the container structure update information Msg.1' is generated corresponding to a change of the structure of the container hierarchy. "MessageID" (message ID) is an integer that is incremented by 1 whenever the container structure update information Msg.1' is generated. In the following description, the above-described container structure update information Msg.1 is substituted with the container structure update information Msg.1'.

The transmitting side replicater 12 generates leaf update information Msg.x1' that is a message to which a filtering mask corresponding to the container hierarchy has been added at step S46 of the flow chart shown in Figs. 18A and 18B. The transmitting side replicater 12 broadcasts the generated leaf update information Msg.x1' to the receiving side replicater 17. Before the receiving side replicater 17 performs a filtering process for the leaf update information Msg.x1', the receiving side 3 should have designated of a target portion of the container hierarchy that the receiving side client 15 requires.

According to the embodiment of the present invention, the receiving side replicater 17 generates a target mask list that lists masks for processing a target container hierarchy.

Next, with reference to Figs. 23A and 23B, a

target mask will be described. First of all, a directory structure as shown in Fig. 23A is assumed. It is assumed that the directory structure shown in Fig. 23A is composed of only container entries except for a root entry at the highest hierarchical level. In Fig. 23A, a single square represents a container entry, whereas a concentric square represents a container entry that the user designates for the filtering process performed by the receiving side client 15. In Fig. 23A, a numeral in each entry represents a mask value assigned thereto.

As shown in Fig. 23A, container entries designated by the user are assigned masks 1 to 5 for the filtering process performed by the receiving side client 15. In the directory structure, the mask values of the total mask length of the masks 1, 2, 3, 4, and 5 are "000", "0010", "010", "1000", and "10010", respectively.

Fig. 23B shows an example of a target mask list that lists the designated masks. The target mask list is composed of a schema version that identifies the directory structure and a list of mask values designated by the receiving side client 15. In other words, the target mask list is a list valid for only the directory structure represented by the schema version.

Fig. 24 is a flow chart showing a process for

generating a target mask list. This process is executed by the receiving side replicater 17. At step S70, the receiving side replicater 17 receives container structure update information Msg.1'. At step
5 S71, it is determined whether or not the container structure update information Msg.1' has been received first time. When the determined result at step S71 is Yes (namely, the container structure update information Msg.1' has been received first time), the flow advances to step S73.

At step S73, the message ID contained in the received container structure update information Msg.1' is stored as a copy 7 to the storing medium or the recording medium such as a memory or a hard disk of the
15 receiving side replicater 17.

At step S74, corresponding to the contents of the received container structure update information Msg.1', a container hierarchy is generated. The receiving side replicater 17 notifies the receiving
20 side client 15 of information that represents the generated container hierarchy so as to prompt the receiving side client 15 for selecting a container entry to be designated. For example, the receiving side client 15 causes a predetermined displaying means
25 to display information corresponding to the supplied container hierarchy. The user selects a required container entry with reference to the information

displayed on the displaying means. The selected container entry information is supplied from the receiving side client 15 to the receiving side replicater 17.

5 A container entry may be designated by other than the user. In other words, the receiving side client 15 may store container entry information inquired by the user, learn the user's favorites corresponding to the stored information, and automatically select a container entry corresponding to the learnt result. Alternatively, a container entry may be designated in a combination of user's direct selection and automatic selection using such a learning process.

10 After a container entry has been selected at step S74, the flow advances to step S75. At step S75, a filtering mask corresponding to the selected container hierarchy is designated. A list of the designated filtering masks is stored as a target mask list to the recording medium or the storing medium such as a memory or a hard disk of the receiving side replicater 17.

15 On the other hand, when the determined result at step S71 is No (namely, the container structure update information Msg.1' has been received not first time), the flow advances to step S72. At step S72, it is determined whether or not the message ID contained

in the received container structure update information
Msg.1' is the same as the message ID stored as copy 7
in the storing medium at step S73.

When the determined result at step S72 is Yes
5 (namely, they are the same), the flow returns to step
S70. On the other hand, when the determined result at
step S72 is No (namely, they are not the same), the
flow advances to step S74. At step S74, the message ID
contained in the newly received container structure
10 update information Msg.1' is stored to the storing
medium instead of the old message ID. Corresponding to
the container structure update information Msg.1' that
has been newly received, the following process is
performed.

15 Fig. 25 is a flow chart showing a process for
selectively receiving leaf update information Msg.x1'
(that has been broadcast) corresponding to a target
mask list generated in the process of the flow chart
shown in Fig. 24. The receiving side replicater 17
20 selectively receives leaf update information Msg.x1'
having a filtering mask listed in the target mask list
from the leaf update information Msg.x1' that has been
broadcast through the broadcasting network 2.
Corresponding to the leaf update information Msg.x1'
25 that has been selectively received, the process of step
S32 of the flow chart shown in Fig. 17 is executed.

In Fig. 25, at step S80, the receiving side

replicater 17 receives leaf update information Msg.xl' that has been broadcast through the broadcasting network 2. The receiving side replicater 17 references the target mask list stored in the storing medium and determines whether or not the filtering mask contained in the received leaf update information Msg.xl' is contained in the target mask list. When the determined result at step S81 is No (namely, the filtering mask is not contained in the target mask list), the flow returns to step S80.

On the other hand, when the determined result at step S81 is Yes (namely, the filtering mask is contained in the target mask list), the flow advances to step S82. At step S82, it is determined whether or not the leaf update information Msg.xl' has been received first time. When the determined result at step S82 is Yes (namely, the leaf update information Msg.xl' has been received first time), the flow advances to step S84. The message ID contained in the received leaf update information Msg.xl' is stored as a copy 8 to the recording medium or the storing medium such as a memory or a hard disk of the receiving side replicater 17. Thereafter, the flow advances to step S85. At step S85, the received leaf update information Msg.xl' is selected as a target of the process of the receiving side replicater 17.

On the other hand, when the determined result

at step S82 is No (namely, the leaf update information
Msg.x1' has been received not first time), the flow
advances to step S83. At step S83, it is determined
whether or not the message ID contained in the received
5 leaf update information Msg.x1' is the same as the
message ID stored as copy 8 to the storing medium at
step S84.

When the determined result at step S83 is Yes
(namely, they are the same), the flow returns to step
10 S80. On the other hand, when the determined result at
step S83 is No (namely, they are not the same), the
flow advances to step S84. At step S84, the message ID
contained in the received leaf update information
Msg.x1' is stored to the storing medium instead of the
15 old message ID. Corresponding to the newly received
leaf update information Msg.x1', the next process is
performed.

As described above, only a user's favorite
portion of the directory structure managed by the
20 transmitting side server 11 can be stored and updated
by the receiving side server 16. Thus, the storing
medium that stores the directory structure can be
effectively used in the receiving side server 16. In
addition, the storage cost of the directory structure
25 in the receiving side server 16 can be suppressed.
Moreover, the processing efficiency of the receiving
side client 15 corresponding to a search request for

contents data stored in the receiving side server 16 can be remarkably improved.

In the above-described embodiment, the mask length of a mask assigned to each container entry is variable. However, the present invention is not limited to such an example. According to the present invention, the mask length may be a fixed length (for example on the order of bytes).

Next, the setting methods of the above-described overall structure information notification period timers T_1 and T_1' will be described. As was described above, different time periods may be set to the overall structure information notification period timer T_1 used for deciding the timing of the broadcast of the container structure update information Msg.1' and to the overall structure information notification period timer T_1' used for deciding the timing of the broadcast of the leaf update information Msg.x1'. In addition, the time periods that are set to the timers T_1 and T_1' can be changed at any time point.

According to the embodiment of the present invention, the transmitting side 1 (transmitting side replicater 12) monitors the operating state of the receiving side 3 (receiving side replicater 17) in a predetermined manner and designates time periods to be set to the timers T_1 and T_1' corresponding to the monitored result. The timers T_1 and T_1' are set to

different time periods that vary in each time zone corresponding to the operating state of the receiving side 3.

Fig. 26 is a flow chart showing an example of a process for setting time periods of the overall structure information notification period timers T_1 and T_1' . At step S140, the receiving side replicater 17 monitors the local operating state. In other words, the receiving side replicater 17 monitors the operating state at intervals of a predetermined time period. The chronological fluctuation of the operating state is stored to the recording medium or the storing medium such as a memory or a hard disk of the receiving side replicater 17. The operating state is obtained by cumulating the time period of the receiving process for two types of update messages in each time zone of the receiving side replicater 17.

The receiving side replicater 17 notifies the transmitting side replicater 12 of data that represents the operating state of the receiving side replicater 17 at step S141. The operating state information is transmitted from the receiving side replicater 17 to the transmitting side replicater 12 through the bidirectional network 4.

The transmitting side replicater 12 receives the operating state information of the receiving side replicater 17 transmitted through the bidirectional

network 4 and performs a predetermined statistic process corresponding to the received operating state information (at step S142). As an example, the statistic process is performed by cumulating the operating state information transmitted from a plurality of receiving side replicaters 17 at intervals of a predetermined time period. As the result of the statistic process, the statistic information of the chronological variation of the operating state of the receiving side replicater 17 is obtained. The obtained statistic information of the chronological variation is stored to the transmitting side replicater 12.

At step S143, the transmitting side replicater 12 sets the overall structure information notification period timers T_1 and T_1' corresponding to the result of the statistic process performed at step S142.

Now, it is assumed that the result of the statistic process performed at step S142 is a chronological variation as shown in Fig. 27. In Fig. 27, the horizontal axis represents time of one day, whereas the vertical axis represents the operating ratio of the receiving side replicater 17. The area b represents a time zone of which the operating ratio of the receiving side replicater 17 is high. The areas a and c represent time zones of which the operating ratio of the receiving side replicater 17 is relatively low.

Corresponding to the statistic results shown in Fig. 27, the overall structure information notification period timers T_1 and T_1' are set for each of the areas a, b, and c. The operating ratio of the receiving side replicater 17 in the area b is higher than that in the areas a and c. It is considered that the access ratio of the receiving side 3 against the broadcast from the transmitting side 1 is high. Thus, even if the timers T_1 and T_1' are set to large time periods and thereby the broadcast period of the difference update information is long, the probability of which the receiving side 3 drops the broadcast difference update information in the area a is lower than that of the areas a and c.

Thus, as an example, in the area b of which the operating ratio of the receiving side replicater 17 is high, long time periods are set to the timers T_1 and T_1' so as to prolong the broadcast intervals of the difference update information. In the areas a and c, short time periods are set to the timers T_1 and T_1' so as to shorten the broadcast intervals of the difference update information. Thus, according to the embodiment of the present invention, the intervals of the notification of the overall structure information that uses many communication resources can be dynamically varied corresponding to the operating ratio of the receiving side 3. Thus, the notification of the

difference update information of the directory structure can be effectively performed.

According to the above-described embodiment, the statistic data of the operating ratio of the receiving side replicater is obtained corresponding to time zones of one day. However, the present invention is not limited to such an example. For example, the statistic data of the variation information of the operating ratio may be obtained at intervals of one week, one month, or one year. Alternatively, the statistic process for the variation of the operating ratio can be performed in a combination of a plurality of intervals.

As was described above, according to the present invention, the directory structure managed on the transmitting side is broadcast with difference update information of container entries and leaf entries corresponding to a change of the structure. In addition, overall structure information that allows the overall directory structure to be reproduced is transmitted at intervals of a predetermined time period. The intervals of the notification of the overall structure information that uses many communication resources are dynamically varied corresponding to the operating ratio on the receiving side. Thus, the notification of the difference update information of the directory structure can be

effectively performed.

In addition, according to the present invention, a directory structure managed on the transmitting side is broadcast with difference update information of container entries and leaf entries corresponding to a change of the structure. In addition, overall structure information that allows the overall hierarchical structure to be reproduced is transmitted at intervals of a predetermined time period. Thus, the receiving side can synchronize with the transmitting side for a portion of the directory structure desired on the receiving side. In addition, the transmitting side can synchronize with a plurality of receiving sides.

Although the present invention has been shown and described with respect to a best mode embodiment thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions, and additions in the form and detail thereof may be made therein without departing from the spirit and scope of the present invention.

What is claimed is:

1. A transmitting apparatus, comprising:

transmitting means for transmitting the same
contents of update information a plurality number of
5 times, the update information representing that data
has been updated,

wherein the transmission timing of the same
contents of the update information transmitted by said
transmitting means is designated corresponding to
10 operating state information of receiving means that
receives the update information from said transmitting
means.

2. The transmitting apparatus as set forth in
claim 1,

15 wherein the transmission timing is a time
zone in which the update information is transmitted.

3. The transmitting apparatus as set forth in
claim 1,

20 wherein the transmission timing is a time
period of which the update information is transmitted
the plurality number of times.

4. The transmitting apparatus as set forth in
claim 1,

25 wherein the transmitting apparatus is a
transmitting device for transmitting a hierarchical
structure of a directory for hierarchically managing
locations of contents data, comprising:

managing means for managing a hierarchical structure of a directory composed of a container entry and a leaf entry, a container entry containing information in the immediately lower hierarchical level thereof, a leaf entry being disposed in the immediately lower hierarchical level of a container entry, a leaf entry not containing information in the immediately lower hierarchical level thereof;

detecting means for detecting a change of the hierarchical structure of the directory managed by said managing means and obtaining first difference information and second difference information corresponding to the detected result, the first difference information being the difference of container entries, the second difference information being the difference of leaf entries; and

transmitting means for transmitting third difference information for reproducing the hierarchical structure of the directory at a predetermined time period along with the first difference information and the second difference information,

wherein the predetermined time period is variably designated corresponding to the operating state information of a receiving side.

5. The transmitting apparatus as set forth in claim 4,

wherein the predetermined time period is

designated corresponding to chronological variation information of the operating state of the receiving side.

6. The transmitting apparatus as set forth in claim 4, further comprising:

communicating means for communicating with the receiving side,

wherein said communicating means receives the operating state information from the receiving side.

7. The transmitting apparatus as set forth in claim 4,

wherein the third difference information is composed of information of only container entries of the hierarchical structure of the directory.

8. The transmitting apparatus as set forth in claim 7,

wherein the predetermined time period is a time period that is a multiple of the time period of which the first difference information is transmitted.

9. The transmitting apparatus as set forth in claim 4,

wherein the third difference information is composed of information of only leaf entries in the immediately lower hierarchical level of each of container entries.

10. The transmitting apparatus as set forth in claim 9,

wherein the predetermined time period is a time period that is a multiple of the time period of which the second difference information is transmitted.

11. A transmitting method, comprising the step of:

transmitting the same contents of update information a plurality number of times, the update information representing that data has been updated,

wherein the transmission timing of the same contents of the update information transmitted at the transmitting step is designated corresponding to operating state information of receiving means that receives the update information from said transmitting means.

12. The transmitting method as set forth in claim 11,

wherein the transmitting method is a method for transmitting a hierarchical structure of a directory for hierarchically managing locations of contents data, the method comprising the steps of:

managing a hierarchical structure of a directory composed of a container entry and a leaf entry, a container entry containing information in the immediately lower hierarchical level thereof, a leaf entry being disposed in the immediately lower hierarchical level of a container entry, a leaf entry not containing information in the immediately lower

hierarchical level thereof;

detecting a change of the hierarchical structure of the directory managed at the managing step and obtaining first difference information and second difference information corresponding to the detected result, the first difference information being the difference of container entries, the second difference information being the difference of leaf entries; and

transmitting third difference information for reproducing the hierarchical structure of the directory at a predetermined time period along with the first difference information and the second difference information,

wherein the predetermined time period is variably designated corresponding to the operating state information of a receiving side.

13. A receiving apparatus for receiving a hierarchical structure of a directory for hierarchically managing the locations of contents data that is transmitted, comprising:

receiving means for receiving first difference information, second difference information, and third difference information, the first difference information being obtained by detecting a change of container entries, the second difference information being obtained by detecting a change of leaf entries, the directory being composed of container entries and

leaf entries, a container entry containing information in the immediately lower hierarchical level thereof, a leaf entry not containing information in the immediately lower hierarchical level thereof, the third difference information being transmitted at a predetermined time period, the third difference information being capable of reproducing the hierarchical structure of the directory; and

managing means for managing the hierarchical structure of the directory formed corresponding to the first difference information, the second difference information, and the third difference information received by said receiving means,

wherein local operating state information of the receiving apparatus is monitored and transmitted.

14. The receiving apparatus as set forth in claim 13, further comprising:

communicating means for communicating with a transmitting side that transmits the third difference information,

wherein said communicating means transmits the operating state information to the transmitting side.

15. The receiving apparatus as set forth in claim 13,

wherein the predetermined time period is designated on the transmitting side that transmits the

third difference information corresponding to the
operating state information.

16. The receiving apparatus as set forth in claim
13,

5 wherein the third difference information is
composed of information of only container entries of
the hierarchical structure of the directory.

17. The receiving apparatus as set forth in claim
16,

10 wherein the predetermined time period is a
time period that is a multiple of the time period of
which the first difference information is transmitted.

18. The receiving apparatus as set forth in claim
13,

15 wherein the third difference information is
composed of information of only leaf entries in the
immediately lower hierarchical level of each of
container entries.

19. The receiving apparatus as set forth in claim
20 18,

wherein the predetermined time period is a
time period that is a multiple of the time period of
which the second difference information is transmitted.

20. A receiving method for receiving a
25 hierarchical structure of a directory for
hierarchically managing the locations of contents data
that is transmitted, comprising the steps of:

receiving first difference information,
second difference information, and third difference
information, the first difference information being
obtained by detecting a change of container entries,
5 the second difference information being obtained by
detecting a change of leaf entries, the directory being
composed of container entries and leaf entries, a
container entry containing information in the
immediately lower hierarchical level thereof, a leaf
10 entry not containing information in the immediately
lower hierarchical level thereof, the third difference
information being transmitted at a predetermined time
period, the third difference information being capable
of reproducing the hierarchical structure of the
15 directory; and

managing the hierarchical structure of the
directory formed corresponding to the first difference
information, the second difference information, and the
third difference information received at the receiving
20 step,

wherein local operating state information of
the receiving apparatus is monitored and transmitted.

21. A transmitting and receiving system,
comprising:

25 transmitting means for transmitting the same
contents of update information a plurality number of
times, the update information representing that data

has been updated; and

receiving means for receiving the update
information transmitted by said transmitting means,

wherein the transmission timing of the same
5 contents of the update information transmitted by said
transmitting means is designated corresponding to
operating state information of said receiving means.

22. The transmitting and receiving system as set
forth in claim 21,

10 wherein the transmission timing is a time
zone in which the update information is transmitted.

23. The transmitting and receiving system as set
forth in claim 21,

15 wherein the transmission timing is a time
period of which the update information is transmitted
the plurality number of times.

24. The transmitting and receiving system as set
forth in claim 21,

20 wherein the transmitting and receiving system
is a system for transmitting a hierarchical structure
of a directory for hierarchically managing locations of
contents data and receiving the transmitted
hierarchical structure, comprising:

25 first managing means for managing a
hierarchical structure of a directory composed of a
container entry and a leaf entry, a container entry
containing information in the immediately lower

hierarchical level thereof, a leaf entry being disposed in the immediately lower hierarchical level of a container entry, a leaf entry not containing information in the immediately lower hierarchical level thereof;

detecting means for detecting a change of the hierarchical structure of the directory managed by said first managing means and obtaining first difference information and second difference information corresponding to the detected result, the first difference information being the difference of container entries corresponding to the detected result, the second difference information being the difference of leaf entries;

transmitting means for transmitting third difference information for reproducing the hierarchical structure of the directory at a predetermined time period along with the first difference information and the second difference information;

receiving means for receiving the first difference information, the second difference information, and the third difference information transmitted by said transmitting means; and

second managing means for managing the hierarchical structure of the directory formed corresponding to the first difference information, the second difference information, and the third difference

information received by said receiving means.

wherein the predetermined time period is
variably designated corresponding to the operating
state information of a receiving side that receives the
third difference information transmitted by said
transmitting means.

25. The transmitting and receiving system as set
forth in claim 24,

wherein the predetermined time period is
designated corresponding to chronological variation
information of the operating state of the receiving
side.

26. The transmitting and receiving system as set
forth in claim 24, further comprising:

communicating means for communicating with a
transmitting side that transmits the third difference
information to the receiving side,

wherein said communicating means transmits
the operating state information from the receiving side
to the transmitting side.

27. The transmitting and receiving system as set
forth in claim 24,

wherein the third difference information is
composed of information of only container entries of
the hierarchical structure of the directory.

28. The transmitting and receiving system as set
forth in claim 27,

wherein the predetermined time period is a time period that is a multiple of the time period of which the first difference information is transmitted.

29. The transmitting and receiving system as set forth in claim 24,

wherein the third difference information is composed of information of only leaf entries in the immediately lower hierarchical level of each of container entries.

30. The transmitting and receiving system as set forth in claim 29,

wherein the predetermined time period is a time period that is a multiple of the time period of which the second difference information is transmitted.

31. A transmitting and receiving method, comprising the step of:

transmitting the same contents of update information a plurality number of times, the update information representing that data has been updated; and

receiving the update information transmitted at the transmitting step,

wherein the transmission timing of the same contents of the update information transmitted at the transmitting step is designated corresponding to operating state information received at the receiving step.

32. The transmitting and receiving method as set forth in claim 31,

wherein the transmitting and receiving method is a method for transmitting a hierarchical structure of a directory for hierarchically managing locations of contents data and receiving the transmitted hierarchical structure, the method comprising the steps of:

managing a hierarchical structure of a directory composed of a container entry and a leaf entry, a container entry containing information in the immediately lower hierarchical level thereof, a leaf entry being disposed in the immediately lower hierarchical level of a container entry, a leaf entry not containing information in the immediately lower hierarchical level thereof;

detecting a change of the hierarchical structure of the directory managed at the first managing step and obtaining first difference information and second difference information corresponding to the detected result, the first difference information being the difference of container entries corresponding to the detected result, the second difference information being the difference of leaf entries;

transmitting third difference information for reproducing the hierarchical structure of the directory

at a predetermined time period along with the first difference information and the second difference information;

5 receiving the first difference information, the second difference information, and the third difference information transmitted at the transmitting step; and

10 managing the hierarchical structure of the directory formed corresponding to the first difference information, the second difference information, and the third difference information received at the receiving step,

15 wherein the predetermined time period is variably designated corresponding to the operating state information of a receiving side that receives the third difference information transmitted at the transmitting step.

ABSTRACT OF THE DISCLOSURE

A transmitting apparatus is disclosed, that
comprises a transmitting means for transmitting the
same contents of update information a plurality number
of times, the update information representing that data
has been updated, wherein the transmission timing of
the same contents of the update information transmitted
by the transmitting means is designated corresponding
to operating state information of receiving means that
receives the update information from the transmitting
means.

Fig. 1





Fig. 3

Fig. 4




Fig. 5




Fig. 6A




Fig. 6B




Fig. 7




Fig. 8




Fig. 9




Fig. 10A

Fig. 10B

Fig. 10C

Fig. 10D

Fig. 10E

Fig. 10F




Fig. 11A




Fig. 11B




Fig. 11C





Fig. 11D



$(1, A, +B)$
 $(1, A, +a)$

$(2, A, -a)$
 $(2, B, +b)$

$(2, B, +C)$
 $(2, C, +C)$

Fig. 12




Fig. 13




Fig. 14




Fig. 15A

Fig. 15

Fig. 15A

Fig. 15B

S2




Fig. 15B




Fig. 16




Fig. 17




Fig. 18A

Fig. 18

Fig. 18A

Fig. 18B

S31




Fig. 19




Fig. 20A




Fig. 20B




Fig. 20C




Fig. 20D




Fig. 21




Fig. 22A





Fig. 22B






Fig. 23A

TARGET MASK LIST
SCHEMA VERSION: XXX
MASK 1: 000
MASK 2: 0010
MASK 3: 010
MASK 4: 10000
MASK 5: 10010

Fig. 23B

Fig. 24




Fig. 25




Fig. 26





Fig. 27



SUGI-T0731

BY EXPRESS MAIL NO. EL254155479US

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者である（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one named is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

TRANSMITTING APPARATUS, TRANSMITTING METHOD, RECEIVING APPARATUS, RECEIVING METHOD, TRANSMITTING AND RECEIVING SYSTEM, AND TRANSMITTING AND RECEIVING METHOD

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。☐ was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on _____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

外国での先行出願

Priority Not Claimed

優先権主張なし

P11-186785
(Number)

(番号)

Japan
(Country)

(国名)

30 June 1999
(Day/Month/Year Filed)
(出願年月日)

Japanese Language Declaration

日本語宣言書

(Number) _____ (Country) _____ (番号) _____ (国名) _____		(Day/Month/Year Filed) _____ (出願年月日) _____	
私は、第 3 5 編米国法典 1 1 9 条 (e) 項に基いて下記の米 国特許出願規定に記載された権利をここに主張いたします。		I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.	
(Application No.) _____ (Filing Date) _____ (出願番号) _____ (出願日) _____		(Application No.) _____ (Filing Date) _____ (出願番号) _____ (出願日) _____	
私は、下記の米国法典第 3 5 編 1 2 0 条に基いて下記の米 国特許出願に記載された権利、又は米国を指定している特許 協力条約 3 6 5 条 (c) に基づく権利をここに主張します。また、 本出願の各種求範囲の内容が米国法典第 3 5 編 1 1 2 条 第 1 項又は特許協力条約で規定された方法で先行する米国特 許出願に開示されていない限り、その先行米国出願書提出日 以降で本出願書の日本国内または特許協力条約国際提出日ま での期間中に入手された、連邦規則法典第 3 7 編 1 条 5 6 項 で定義された特許資格の有無に関する重要な情報について開 示義務があることを認識しています。		I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.	
(Application No.) _____ (Filing Date) _____ (出願番号) _____ (出願日) _____		(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)	
(Application No.) _____ (Filing Date) _____ (出願番号) _____ (出願日) _____		(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)	
私は、私自身の知識に基づいて本宣言書中で私が行なう表 明が真実であり、かつ私の入手した情報と私の信じるところ に基づく表明が全て真実であると信じていること、さらに故 意になされた虚偽の表明及びそれと同等の行為は米国法典第 1 8 編第 1 0 0 1 条に基づき、罰金または拘禁、もしくはそ の両方により処罰されること、そしてそのような故意による 虚偽の表明を行なえば、出願した、又は既に許可された特許 の有効性が失われることを認識し、よってここに上記のごと く宣誓を致します。		I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may be jeopardize the validity of the application or any patent issued thereon.	

Japanese Language Declaration

日本語宣言書

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁護士または代理人として、下記の者を指名いたします。（弁護士、または代理人の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark office connected therewith (*list name and registration number*)

Karl A. Limbach	18,689	Steven M. Everett	30,050	Cameron A. King	41,897
George C. Limbach	19,305	Alfred A. Equitz	30,922	Kyla L. Harnel	41,815
John K. Uilkema	20,282	Charles P. Sammut	28,901	Mayumi Maeda	40,075
Neil A. Smith	25,441	Mark C. Pickenng	36,239	Michael R. Ward	38,551
Veronica C. Devitt	29,375	Patricia Coleman James	37,155	Roger S. Sampson	44,314
Ronald L. Yin	27,607	Kathleen A. Frost	37,326	Charles L. Hamilton	42,524
Gerald T. Sekimura	30,103	Alan A. Limbach	39,749	Andrew V. Smith	43,132
Michael A. Stallman	29,444	Douglas C. Limbach	35,249	Enc N. Hoover	37,355
Philip A. Girard	28,848	Seong-Kun Oh*		J. Thomas McCarthy	22,420
Michael J. Pollock	29,098			Joel G. Ackerman	24,307

* Recognition under 37 CFR 10.91(c)

書類送付先

Send Correspondence to:

**Charles P. Sammut, Esq.
Limbach & Limbach L.L.P.
2001 Ferry Building
San Francisco, CA 94111-4262**

直接電話連絡先：（名前及び電話番号）

Direct Telephone Calls to: (*name and telephone number*)

**Charles P. Sammut
(415) 433-4150**

唯一または第一発明者名

Full name of sole or first inventor:

YASUAKI YAMAGISHI

発明者の署名

日付

Inventor's signature

Date

住所

Residence

Kanagawa, Japan

国籍

Citizenship

Japan

私書箱

Post Office Address

c/o SONY CORPORATION
7-35, Kitashinagawa 6-chome
Shinagawa-ku, Tokyo, 141-0001 JAPAN

Japanese Language Declaration 日本語宣言書	
第二共同発明者	Full name of second joint inventor, if any KAZUHIKO TAKABAYASHI
第二共同発明者 日付	Second inventor's signature Date
住所	Residence Tokyo, Japan
国籍	Citizenship Japan
私書箱	Post Office Address c/o SONY CORPORATION 7-35, Kitashinagawa 6-chome Shinagawa-ku, Tokyo, 141-0001 JAPAN
第三共同発明者	Full name of third joint inventor, if any KAZUO HARAOKA
第三共同発明者 日付	Third inventor's signature Date
住所	Residence Kanagawa, Japan
国籍	Citizenship Japan
私書箱	Post Office Address c/o SONY CORPORATION 7-35, Kitashinagawa 6-chome Shinagawa-ku, Tokyo, 141-0001 JAPAN
第四共同発明者	Full name of fourth joint inventor, if any YOSHIHISA GONNO
第四共同発明者 日付	Fourth inventor's signature Date
住所	Residence Kanagawa, Japan
国籍	Citizenship Japan
私書箱	Post Office Address c/o SONY CORPORATION 7-35, Kitashinagawa 6-chome Shinagawa-ku, Tokyo, 141-0001 JAPAN

第五共同発明者	Full name of fifth joint inventor, if any FUMIHIKO NISHIO
第五共同発明者 日付	Fifth inventor's signature Date
住所	Residence Tokyo, Japan
国籍	Citizenship Japan
私書箱	Post Office Address c/o SONY CORPORATION 7-35, Kitashinagawa 6-chome Shinagawa-ku, Tokyo, 141-0001 JAPAN